

# Fire Rated Internal Door-Sets

- EMERGENCY EXIT
- PERSONNEL DOORS

SUITABLE FOR INTERNAL USE ONLY

# UNIQUE RANGE FEATURES

10-12 days lead time\* Up to 2.96m high 1 year warranty Fast quotes \*Subject to manufacturing and stock availability







**Firedor is fire-rated** between 30 and 240 minutes to BS EN 1634-1 for internal use only and smoke-rated to BS EN 1634-3. The single personnel door-sets are designed to enable internal entry and exit. Each is built to order, individually constructed with a choice of hardware, frame, threshold and panel options - information sheets available on request.

# Fire Rated Internal Door-sets

## **Rebate frame**

(See Figs. 1, 2, 3 & 4) Typical door configuration consists standard rebate frame assembly, for single door-sets. Made from lightweight, high tensile 'Rustec' steel and powder coat finish, it also has an "Adjust-2-Fit" side expander system that offers 6

adjustable fixing positions.

Various frame depths and styles available - including double rebate frames (see frame specification sheet).

Manufactured from 1.5 mm thick 'Rustec' steel.

Single rebate 104mm wide frame with additional rebate for flush lip.

A minimum of six fully adjustable fixing points are provided to each jamb - extra fixings available on request.

Unique 'Adjust-2-fit' side channels with each frame.

### Leaf

44mm door leaf thickness, fitted with a flush lipped astragal for added security. Comprising of  $2 \times 1.2$ mm 'Rustec' steel sheets, the leaf is internally bonded with a dutch fold stitch welded system providing greater stability and protection against de-lamination.

42mm thick 'Hexatex' core.


## Industrial door threshold - 96mm

(See Fig. 3) Standard aluminium threshold is Part M compliant and is fitted with a seal for outward opening door-sets.



door configuration

Single door	Size range
Width	Up to 1400mm
Height	Up to 2960mm



Weight

Finish

available.

Seals

31kg/m<sup>2</sup> with 'Hexatex' core.

BS 7352 Grade 13 stainless steel, twin bearing

dog bolts are fitted as standard with CE marking.

Supplied inclusive of a powder coated finish in a

Strongdor self adhesive neoprene teardrop seal

Side panels and over panels (optional)

Solid and glazed side and over panels available.

standard colour. Full range of RAL and BS colours

template drilled butt hinges with integral high security

Door ironmongery

Other hardware available.

provided as standard.

Double door	Size range
Width	Up to 2700mm
Height	Up to 2960mm


#### Large bespoke sizes also available upon request.


Other options on request.




# EXTERNAL FIRE-RATED AVAILABLE!

EN16034 COMPLIANT












# **Glazed Vision Panels**

Our vision panels are produced in various panel formats and sizes, some of which can be fire rated, we offer a choice of glazing options depending on the doors application. Please refer to the company website for glazed vision panels.



# Louvre Panels

Designed to increase airflow in areas that need efficient vetilation, louvre door, side, over panels and walls offer a flexible solution without compromising security or structural integrity. Please refer to the company website for louvre panels.



# Side and Over Panels

Extend your door using made to measure panels offered as either solid, glazed or louvred. All powder coated to perfectly match your door. Please refer to the company website for side and over panels.

CE

# **Hardware options**

View our poular items of door furniture and security hardware. Please refer to the company website for hardware .



FIREDOR | Fire-Rated Door Sets