

# Rutland Door Closer Options

## HARDWARE OPTIONS

### TECHNICAL SPECIFICATIONS

#### Rutland TS.5204 Door Closer



Ideal for Doc M contracts, variable by power and easy to fit. Successfully third party tested to BS EN1154 & CE marked to power size 2-4. Variable power size EN2-4, does doors up to 80kg & 1100mm wide. Assists BS8300 for DocM contracts – helping to assist door sets with ease of opening. Universal application – can be fitted in Standard, Parallel arm or Transom fitting position

- 3 Adjustable closing speed, latch speed & back check
- 3 Available in Silver, Gold, Satin Nickel, Polished Nickel & Polished Brass
- 3 Hold Open arm-set (not suitable for fire doors)
- 3 Delayed action

#### Rutland TS.9206 Door Closer



This highly efficient door closer has immense torque and control, ideal for heavy usage. It comes with a slimline appearance. Successfully third party tested to BS EN1154 & CE marked to power size 2-6. Variable power adjustable EN2-6 – does doors up to 120kg & 1400mm wide. Universal application – can be fitted in Standard, Parallel arm or Transom fitting position

- 3 Comes standard with delayed action & back check
- 3 Hold open arm-sets available (non suitable for fire doors)

#### Rutland TS.9205 Door Closer



TS9205



TS9205 Marine

Engineered to last and known for its high efficiency and ease of opening. They can be adjusted to suit almost all types of door Successfully third party tested to BS EN1154 & CE marked to power size 2-5. Variable power adjustable EN2-5 – does doors up to 110kg & 1250mm wide. Assists BS8300 for DocM contracts – helping to assist door sets with ease of opening. Universal application – can be fitted in Standard, Parallel arm or Transom fitting position. Available with delayed action & back check. Finishes include an anti-corrosion MARINE316.

- 3 Fire tested to EN1634-1
- 3 Hold open arm-sets available
- 3 IP.95M needed for un-insulated steel doors
- 3 Delayed action & back check

#### Rutland ITS.11204 Concealed Cam Action Door Closer



Cam action door closer with slimline mechanism (32mm), fire tested in a 44mm fire door. Concealed closer with a cam and roller mechanism which makes it perfect for compliance with Approved Document M and BS 8300 recommendations. When the door is closed, it is fully concealed. Successfully third party tested to BS EN1154 & CE marked to power size 2-4 Variable power adjustable EN2-4 – does doors up to 80kg & 1100mm wide. Assists BS8300 for DocM contracts – helping to assist door sets with ease of opening.

- 3 Hold open clips available