



Door pictured is outward opening

Securid^{or}

Secured by Design PAS 24 Steel Security Doors

- MANUAL AND ELECTRIC LOCKING

SUITABLE FOR SECURITY
OF BUILDINGS

UNIQUE FEATURES

10-12 day lead time*

Up to 3.24m high with solid/glazed over panel

1 year warranty

Fast quotes

*Subject to manufacturing and stock availability



Strongdor Secured by Design door-sets are certified to comply with the standards set by the national Police initiative to improve the security of buildings and their immediate surroundings, to provide safe places to live, work, shop and visit.

These door-sets offer greater protection to bin stores, plant rooms and access to communal areas and can be used on both residential and commercial developments that require the peace of mind that comes with Secured by Design compliance.

Secured by Design



Official Police Security Initiative

Leaf

44mm door leaf thickness, fitted with an integrated astragal for added security. Comprising of 2 x 1.2mm steel sheets, the leaf skins are mechanically interlocked and internally bonded providing greater stability and protection against de-lamination.

42mm thick 'Hexatex' core.

Insulated core as low as 1.5 U-value.

Standards

Certified to: PAS 24:2016 Enhanced security performance requirement for door-sets and windows in the UK. Door-sets and windows intended to offer a level of security suitable for dwellings and other buildings exposed to comparable risk. BM Trada Certificate 050/250.

Types

Classified as single and double lead, over panel, fully glazed, hinged, internally glazed, inward opening, louvre, outward opening, side panel/vision panel, with or without letter plate.

Earth Bonding Upgrade ⚡

Boost safety and meet industry standards with our new Earth Bonding upgrade. This feature enhances protection by providing a secure grounding point, offering peace of mind in environments where electrical safety is critical.

Threshold

AM3 inward opening or AM5 outward opening threshold available on request.

Acoustic Rating

Up to 39dB rating.

Finish

Supplied inclusive of a powder coated finish in a standard colour. Full range of RAL and BS colours available.

Options and upgrades

Manual and electric locking

Glazed and louvre panels available.

Max door sizes

(excluding side and over panels)

Structural Opening	Single Door	Double Door
Width	Up to 1360mm	Up to 2502mm*
Height	Up to 2250mm	Up to 2250mm

* For panic exit doors, the maximum width is up to 2610mm.



Manual Locking Options

Lock case and cylinders



Briton 5420 Sashlock Radius

Our most popular and reliable lockcase for both it's security and longevity. Cylinder latch function enables the cylinder to withdraw the deadbolt on the first turn and the latch on the second turn of the cylinder.




3* Euro Kitemarked Double Cylinder

3 star high security cylinder to comply with the British Kitemark standard. Meets the Sold Secure Diamond Standard with high security 6 pin cylinder suitable for any external door to deter potential attack.

Panic Hardware

MICO Modular



Electric Locking Options

V lock and strike case



The ES8000, also known as the V-lock is a high torque motorised bolt that moves from the vertical position to the horizontal state when locked. The bolt moves into the V shaped strike plate pulling the door aligned with the lock.

Optional Hardware

